

Product Code: APWIFIDSBLK2

Description: Wired Wi-Fi Door Station (Black) with Record Facility & Door Chime



Door Station

Sensor Size	1/2.7"
Viewing Angle	140o
Sensitivity	1 Lux
IR LED	5 pcs
IR distance	5 Metres
Memory	8GB MicroSD (Supplied) 128GB Max.
Construction	Aluminum and Polycarbonate
Weight	170g
Dimensions	55mm (W) x 132mm (H) x 24mm (D)

Video & Audio

Resolution	1080p
Audio	Full Duplex

Installation Environment

Working Temperature	-10°C- + 40°C
Ingress Protection	IP55

Power & Relays

Input Supply	9-48V DC (12V DC UK plug-in adaptor supplied)
Lock Relay	2A 24V DC
Chime Relay	2A 24V DC

Network

Wi-Fi	2.4GHz Connection
System Range	150 Metres to RF Chime

RF Door Chime

Power	3x AA Batteries (supplied)
Indication	LED and Audio
Weight	146g
Dimensions	60mm (W) x 150mm (H) x 26mm (D)

Construction

Housing Material	ABS
-------------------------	-----

Installation Environment

Working Temperature	-10°C- + 40°C
Ingress Protection	IP20

Components Supplied

Door station and wall bracket
2 x Fixing screws & wall plugs
Plug-in power adaptor
8GB MicroSD card
DC power, relay contact extension cables & terminal screw driver
Door chime & 3 x AA batteries
Quick start guide

Compatible Products & Accessories

ENTERD	12V DC Flush Door Strike (Rim Lock Only)
ENTERD-YLR	12V DC Surface Electronic Lock Release for Yale Type Locks
EVBPSSBB	12V DC 1.5A Multi Output Boxed Power Supply with Battery Back Up Facility
EV-EBG	Surface Mounting Green Call Point 'Emergency Door Release'
EV-EXIT	Push to Exit Release Button
EVEXITM	Mushroom Exit Button
EVEXITMIP55	Mushroom Exit Button - IP55
EV-ML-250	Electromagnetic Lock (250Kg)
EV-ML-500XT	Electromagnetic Lock (500Kg) - IP67

Additional Information

Ethernet interface available
Alerts user to visitors via smart-phone APP
No subscription or additional fees required
Visitor record function, Smart Detection (Motion Detection)
High Definition colour image and 2-way audio