



ACELED/3M/ST

Centurion LED Bulkhead Maintained / Non-Maintained 6W White



Features

High lumen performance LED polycarbonate bulkhead for increased spacings.

Supplied with self-adhesive legend.

Self-test as standard.

Outperforms 8W T5 and exceeds performance of Guardian by 56%.

20mm conduit entry positions and rear terminal box entry.

Hinged screwless gear tray for ease of installation.

Viewing distance 18 metres.

50,000 hours average lifetime.

General Information

Lamp Type	LED
Colour / Finish	White
Self Test	Yes
IP Rating	IP65
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Surface
Warranty (Years)	3
CE Mark	Yes
Height / Depth	64
Length / Diameter	352
Width	110
Accessories	ASBP/2

Technical Information

Wattage	6W
Lumens Delivered	151lm (Emergency), 254lm (Standard)
CCT	6500K
Input	230V
Hertz	50/60Hz
Operating Temp	0C° to 45C°

Technical Data - ETIM 6 - Emergency luminaire (EC001957)

Mounting method	Wall surface mounted
With light source	Yes
Lamp power	6 W
Material housing	Plastic
Colour housing	White
Type of indicator	Only single-sided
Labelling type	Sticker
Monitoring equipment	Automatic self test
Voltage type	AC
Nominal voltage	230-230 V
Protection class	I
Degree of protection (IP)	IP65
Length	352 mm
Width	110 mm
Height/depth	64 mm
Luminous flux at emergency operation	150 lm
Recognition distance	18 m
Rated luminous flux acc. IEC 62722-2-1	229 lm
Colour of light	White
Colour temperature	6500-6500 K

Datasheet generated from <http://www.electrika.com> last updated Monday, September 3, 2018 2:36:49 PM

