

FS2126-T BATTERY POWERED MULTI-SENSOR SMOKE ALARM


| | |
|--------------|---|
| Sensor type | Thermoptek Multi-Sensor Optical |
| Battery type | 10 year sealed for life Panasonic lithium |



- **Smart RF Ready** - Fit a Smart RF Radio Module (FS1521W2) to wirelessly interlink up to 50 FireAngel Smart RF products, including FireAngel Connect Gateway
- Connects directly to the **FireAngel Connect Gateway**, providing enhanced diagnostic capabilities and real-time notifications to mobile devices. (Requires FS1521W2 Smart RF Radio Module)
- Thermoptek Multi-Sensor optical sensing technology as used by over 90% of the UK Fire and Rescue Services
- Remote, automated reporting of buzzer status via FireAngel Connect
- Intelligent status monitoring without intrusive standby indicator LED
- Easily accessible central button to for Test / Smart Silence / Locate functions
- Smart Silence allows the alarm to be silenced for up to 10 minutes in the event of a known false alarm. During these 10 minutes if additional smoke is detected the alarm will sound
- Grade F1 as per BS 5839-6:2019

Technical Specification

| | |
|------------------------|---|
| Product Dimensions | 132mm (diameter) x 40.50mm (depth) |
| Supply voltage | 3V DC |
| Battery | 10 year sealed for life Panasonic lithium |
| Technology | Thermoptek Multi-Sensor and Smart RF Ready |
| Alarm sound level | 85dB(A) at 3m (minimum) |
| Installation positions | Wall / Ceiling |
| For use in: | Hallway, Landing, Living Room, Bedroom, Dining Room |
| Operating temperature | +4°C to +38°C |
| Operating humidity | Up to 90% RH non-condensing |
| Storage temperature | -20°C to +60° C |
| Storage humidity | Up to 93% RH non-condensing |
| Plastic material | ABS, UL94 VO fire retardant |
| Warranty | 5 years |
| Master pack quantity | 10 |
| Weight | 150g |
| Certified to | EN14604:2005+AC:2008 |
| Operating Frequency | 868 MHz |



Create a Safety Network

Add a Smart RF Radio Module to wirelessly interlink up to 50 Smart RF devices with a simple 2 step process.




Heat Alarm



CO Alarm



Wireless Alarm Control Unit



Assisted Living Solutions

For further information or sales enquiries, contact your local Specification Manager:
www.fireangel.co.uk/specification-manager