



CEW05LBL/N

5W Standard Emergency Module for Linear LED Luminaire



Product Overview

The Emergency Module for LED Batten Luminaires has been designed for easy installation in a range of Kosnic LED batten luminaires. Kosnic LED batten datasheet will state if the luminaire is compatible with this model of emergency module. The emergency module is designed to be installed with the quick-fit tabs in the luminaire and includes a flat 4-pin connector for easy connection to the LED light source and status indicator in the luminaire. The emergency module will adjust the output within the module's limits to the level required to operate the luminaire and ensure an operation time of three hours. The emergency module has a replaceable lithium-ion battery.

Features

For Kosnic LED battens, where specified on the batten datasheet

For maintained or non-maintained emergency lighting systems

Conforms to EN 61347-1 and EN 61347-2-7

Supplied with connectors for easy wiring into the batten luminaire

Suitable for use in luminaires for high-risk task area lighting

Voltage change-over threshold according to EN 60598-2-22

3 hours rated duration

Li-Ion battery for improved lifespan allowing frequent partial discharge without capacity reduction

Over-charge, over-current, short-circuit and deep discharge protection for battery

Status indicator LED pre-fitted in Kosnic battens

Specifications

Input Current (mA)	35
Input Voltage	220-240Vac
IP Rating	IP20
Ambient Temperature (°C)	-10 to 45

Datasheet generated from <https://www.electrika.com> last updated Wednesday, May 1, 2019 10:05:25 AM

