

Model Name	ESA	ESA	PERI	PERI	LIBRA	VESTA	ELARA
Item nr	6255-CAM gr	6255-CAM wh	6295-CAM gr	6295-CAM wh	6324-CAM wh	ST1906-CAM	ST2671-CAM
Photo							



LIGHT							
Power (total circuit)	25 W	25 W	25 W	25 W	38 W	30 W	18 W
Lumen Output	1530 Lumen	1530 Lumen	2126 Lumen	2126 Lumen	3000 Lumen	1350 Lumen	1000 Lumen
Lumen Source	2350 Lumen	2350 Lumen	2800 Lumen	2800 Lumen	4160 Lumen	2400 Lumen	1540 Lumen
Lumen per watt	61	61	85	85	79	45	56
Angle of light coverage	120°	120°	107°	107°	111°	80°	140°
LED CRI ( colour rendering index)	80	80	80	80	80	80	80
LED Colour Temperature	5000 K	3000 K	3000 K				
LED Life time	50,000 hours						
Adjustable light level	Continuous Light : 0 to 40% Reaction Light: 30 to 100%	Continuous Light : 0 to 40% Reaction Light: 30 to 100%	Continuous Light : 0 to 40% Reaction Light: 30 to 100%	Continuous Light : 0 to 40% Reaction Light: 30 to 100%	Continuous Light : 0 to 40% Reaction Light: 30 to 100%	Continuous Light : 0 to 40% Reaction Light: 30 to 100%	Continuous Light : 0 to 40% Reaction Light: 30 to 100%
Continuous Light Time	DUSK/DAWN 2H 4H 6H 10H						



PIR MOTION SENSOR							
Physical adjustment	Horizontal: 180° Vertical: 25°	Horizontal: 180° Vertical: 25°	NO	NO	NO	No	NO
Detection angle	180°	180°	270°	270°	270°	120°	120°
Detection range	Up to appx 20 metres	Up to appx 20 metres	Up to appx 19 metres	Up to appx 19 metres	Up to appx 19 metres	Up to appx 13 metres	Up to appx 12 metres
Adjustable range	From 1 meter to 20 meters	From 1 meter to 20 meters	From 1.5 meter to 19 meters	From 1.5 meter to 19 meters	From 1.5 meter to 19 meters	From 0 meter to 13 meters	From 0 meter to 12 meters
Nighttime only operation (override)	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Adjustable lux level	Yes, 20 lux to infinity	Yes, 20 lux to infinity	Yes, 20 lux to infinity	Yes, 20 lux to infinity	Yes, 20 lux to infinity	Yes, 20 lux to infinity	Yes, 20 lux to infinity
Adjustable Time on	1-3-10-15 mins	1-3-10-15 mins	1-3-10-15 mins	1-3-10-15 mins	1-3-10-15 mins	1-3-10-15 mins	1-3-10-15 mins
Auto switch off ( off at sunrise)	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Auto reset to security mode	Yes	Yes	Yes	Yes	Yes	Yes	Yes



CAMERA & VIDEO							
Type	CMOS (glass)						
Camera resolution	1/4, 1 mp						
Camera quality	1-megapixel sensor with millions of colors						
Lens angle	110 °	110°	110°	110°	110°	110°	110 °
Lens sensivity	F2.0 aperture						
Night vision	no						
Vertical adjustment	40°	40°	35°	35°	35°	30°	35°
Horizontal adjustment	170°	170°	180°	180°	180°	No	No
Video quality	HD 1280 x 720						
Frames per second	up to 25						
Remote video record	yes						
On board record	Yes						
Storage SD card inside the camera-light	Supplied with 8 GB SD card (supports up to 32GB)	Supplied with 8 GB SD card (supports up to 32GB)	Supplied with 8 GB SD card (supports up to 32GB)	Supplied with 8 GB SD card (supports up to 32GB)	Supplied with 8 GB SD card (supports up to 32GB)	Supplied with 8 GB SD card (supports up to 32GB)	Supplied with 8 GB SD card (supports up to 32GB)
Overwrite facility	Yes						
Snapshot facility	yes						
Snapshot while watching	Yes						
Video record/save and watch at same time	Yes						
Snapshot output format	J-Peg						
Video Image output format	HD Full color 720p H.264	H.264	H.264	H.264	H.264	H.264	H.264
PIR activation	Yes						
Camera Pixel change activation (daytime mode)	Yes						
Pixel and PIR activation	Yes						
Pulse count	Yes, to avoid false triggers						



AUDIO							
Microphone	yes						
Speaker	yes						
Alarm	Built-in siren 100+ decibel						



CONNECTIVITY							
Type	WiFi	WiFi	WiFi	WiFi	WiFi	WiFi	WiFi
Wireless network	802.11 /b/g/n, 2.4Ghz WEP, WPA and WPA2 supported	802.11 /b/g/n, 2.4Ghz WEP, WPA and WPA2 supported	802.11 /b/g/n, 2.4Ghz WEP, WPA and WPA2 supported	802.11 /b/g/n, 2.4Ghz WEP, WPA and WPA2 supported	802.11 /b/g/n, 2.4Ghz WEP, WPA and WPA2 supported	802.11 /b/g/n, 2.4Ghz WEP, WPA and WPA2 supported	802.11 /b/g/n, 2.4Ghz WEP, WPA and WPA2 supported
Wifi speed (upload/download)	Best performance with 2 Mbps where the camera-light is installed	at least 2 Mbps where the camera-light is installed	at least 2 Mbps where the camera-light is installed	at least 2 Mbps where the camera-light is installed	at least 2 Mbps where the camera-light is installed	at least 2 Mbps where the camera-light is installed	at least 2 Mbps where the camera-light is installed
Aerial	Built in to product	Built in to product	Built in to product	Built in to product	Built in to product	out of the product	Built in to product
Range from camera-light to router (in open air or line of sight)	30 Mtrs	30 Mtrs	30 mtrs	30 mtrs	30 mtrs	30 mtrs	30 mtrs



APP							
Free Download	Yes, App Store & Google play						
Android and iPhone operation	Yes						
Add, modify or delete cameras manually or with wizard or QR-code	Yes						
Maximum cameras that can be added to system	Unlimited (subject to device)						
Audible alarm	Yes						
Two way voice	Yes						
Background noise elimination	Yes						
System status	Yes (various)						
Device management controls	Yes						
System re-set facility	yes						
Operation to various devices Smartphone, Tablet, PC,...	no, only in IOS and Android, not support in pc	no, only in IOS and Android, not support in pc	no, only in IOS and Android, not support in pc	no, only in IOS and Android, not support in pc	no, only in IOS and Android, not support in pc	no, only in IOS and Android, not support in pc	no, only in IOS and Android, not support in pc
Fast set up	QR- code and serial number						
Adjustable camera settings	Yes						
Wireless settings (WPA)	yes						
Number of cameras the system can handle	Unlimited subject to device						
Multiple device settings	Yes						
Schedule or recording sessions	Yes, Auto- record (camera always on)						
Record and file management and search setting	yes						
Live notifications	yes						
Media viewer	Windows media player						
Time and date Generation	Yes (on Phone)						
E-mail alerts	No						

### PRODUCT INFO

Colour	Dark Grey	White	Dark Grey	White	White	Stainless steel	Stainless steel
Material	Aluminum+PC	Aluminum+PC	Aluminum+PC	Aluminum+PC	Aluminum+PC	Stainless steel+Aluminum+PC	Stainless steel+Aluminum+PC
Weatherproof	IP54	IP54	IP44	IP44	IP44	IP54	IP44
Adjustable head horizontal	170 degree	170 degree	90 degree	90 degree	90 degree	no	no
Adjustable head vertical	40 degree	40 degree	45 degree	45 degree	45 degree	no	no
Product guarantee	5 years	5 years					
Controls on camera-light	No, all on your phone	No, all on your phone					



SUPPORT							
Support pages & FAQ	Yes, in App & on <a href="http://www.lutec.net">www.lutec.net</a>						
Contact	<a href="mailto:service@lutec.net">service@lutec.net</a>						
Help Center	under construction						
Languages	English, French , German, Italian, Spanish, Dutch						
Instruction manual	Yes, included in the box						



LOGISTIC INFO							
Bar code	6939412040417	6939412040400	6939412040318	6939412040301	6939412042305	6939412042503	6939412042602
Full Color Unit- Box	yes	yes	yes	yes	yes	yes	yes
Size Unit Box	14.5*26*40 cm	14.5*26*40 cm	25.5*26*40 cm	25.5*26*40 cm	25.5*26*40 cm	11*26*40 cm	11*26*40 cm
Volume Unit Box	15.080 cm³	15.080 cm³	26.520 cm³	26.520 cm³	26.520 cm³	1.440 cm³	1.440 cm³
Net Weight Unit Box	1.10 kg	1.10 kg	1.10 kg	1.10 kg	1.30 kg	1.40 kg	0.90 kg
Total Weight Unit Box	2.00 kg	2 kg	2.40 kg	2.40 kg	2.60 kg	2.13 kg	1.66 kg
Size Outer Carton	31.5*41.5*53.5 cm	31.5*41.5*53.5 cm	53.5*41.5*53.5 cm	53.5*41.5*53.5 cm	53.5*41.5*53.5 cm	24.50*41.5*54.0 cm	24.50*41.5*54.0 cm
Volume Outer Carton	0.070 m³	0.070 m³	0.119 m³	0.119 m³	0.119 m³	0.060 m³	0.060 m³
Net Weight Outer Carton	8.00 kg	8.00 kg	9.60 kg	9.60 kg	10.40 kg	8.50 kg	6.65 kg
Total Weight Outer Carton	9.30 kg	9.30 kg	11.50 kg	11.50 kg	12.30 kg	9.40 kg	7.55kg
Pcs per Outer Carton	4	4	4	4	4	4	4