



## AKTLED/3M/ST

Kite LED Emergency Bulkhead Maintained / Non-Maintained 3W White



## Features

Modern ultra-slim profile IP65 LED polycarbonate bulkhead.

Self-test as standard.

Aesthetically designed for modern appearance.

Supplied with self-adhesive legend.

20mm side and rear cable entries.

Hinged screwless gear tray for ease of installation.

Viewing distance 20 metres.

## General Information

Lamp Type	LED
Colour / Finish	White
Self Test	Yes
IP Rating	IP65
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Surface
Warranty (Years)	3
CE Mark	Yes
Height / Depth	45
Length / Diameter	270
Width	120
Accessories	ASBP/1

## Technical Information

Wattage	4W
Lumens Delivered	79lm (Emergency), 182lm (Standard)
CCT	6500K
Input	230V
Hertz	50/60Hz
Operating Temp	0C° to 45C°

## Technical Data - ETIM 6 - Emergency luminaire (EC001957)

<b>Mounting method</b>	Wall surface mounted
<b>With light source</b>	Yes
<b>Lamp power</b>	3 W
<b>Material housing</b>	Plastic
<b>Colour housing</b>	White
<b>Material cover</b>	Plastic, structured
<b>Type of indicator</b>	Only single-sided
<b>Labelling type</b>	Sticker
<b>Monitoring equipment</b>	Automatic self test
<b>Voltage type</b>	AC
<b>Nominal voltage</b>	230-230 V
<b>Protection class</b>	I
<b>Degree of protection (IP)</b>	IP65
<b>Length</b>	270 mm
<b>Width</b>	120 mm
<b>Height/depth</b>	45 mm
<b>Recognition distance</b>	20 m
<b>Rated luminous flux acc. IEC 62722-2-1</b>	123 lm
<b>Colour of light</b>	White
<b>Colour temperature</b>	6500-6500 K
<b>Luminous flux at emergency operation</b>	68 lm

Datasheet generated from <http://www.electrika.com> last updated Monday, September 3, 2018 2:36:49 PM

