

## SWA Gland Kits

product code	description	pack quantity
63G20SBW	20mm Reduced Indoor	2
63G20SCW	20mm Reduced Outdoor	2
63G20BW	20mm Indoor	2
63G20CW	20mm Outdoor	2
63G25BW	25mm Indoor	2
63G25CW	25mm Outdoor	2
63G32BW	32mm Indoor	2
63G32CW	32mm Outdoor	2
63G40BW	40mm Indoor	1
63G40CW	40mm Outdoor	1
63G50BW	50mm Indoor	1
63G50CW	50mm Outdoor	1
63G63BW	63mm Indoor	1
63G63CW	63mm Outdoor	1
63G75BW	75mm Indoor	1
63G75CW	75mm Outdoor	1



Each kit supplied with glands, locknuts, earth tags & shrouds

For use with PVC-SWA-PVC 600/1000V cable with stranded copper conductor to BS5467

All kits - CE marked

Independent UK test house certification to BS6121

For SWA Cleats refer to Cable Fixings Section

## Gland Selection Chart

Cable Size	Number of Cores												
	1	2	3	4	5	7	10	12	19	27	37	48	
1.5mm	-	20S	20S	20S	20S	20S	20	20	25	25	32	32	
2.5mm	-	20S	20S	20S	20S	20	25	25	25	32	32	40	
4mm	-	20S	20S	20	20	25	25	25	32	40	-	-	
6mm	-	20S	20	20									
10mm	-	20	25	25									
16mm	-	25	25	25									
25mm	-	25	25	32									
35mm	-	32	32	40									
50mm	20	32	32	40									
70mm	25	32	40	40									
95mm	25	40	40	50									
120mm	25	40	50	50									
150mm	32	40	50	50									
185mm	32	50	50	63									
240mm	40	50	63	63									
300mm	40	63	63	75									
400mm	50	63	75	75									

The gland sizes recommended in this chart are for guidance only and are based on cables manufactured to BS5467

In accordance with BS6121 actual cable dimensions must be used for gland selection

## Nylon Male Compression Glands

(IP68 Rated)

product code	size	colour	pack quantity
63MCG20B	20mm	Black	10
63MCG20W	20mm	White	10
63MCG25B	25mm	Black	10
63MCG25W	25mm	White	10

