

# PowerMaster-360R

## Modern Wireless Alarm and Home Automation Gateway



### Features that Make a Difference:

- EN regulated alarm system
- Modular security and home automation system, supporting:
  - PowerG Technology for security devices
  - Z-Wave radio for home automation devices (optional)
  - Wi-Fi module for IP camera support (optional)
- Field replaceable 2G/3G cellular module for network communication (optional)
- Professional panel that can be installed out of sight, controlled by wireless devices
- Robust solution with battery and cellular link backup
- Built-in Siren
- Touchscreen keypad
- Accommodates more than 120 wireless devices:
  - Up to 64 zones
  - Up to 10 PIR cameras, 32 keypads, 32 keyfobs, 8 sirens, 4 repeaters
- Extensive range of PowerG peripherals for every application
- Remote configuration and diagnostics with system status indications
- Part of a solution that includes 3rd party cloud-based platform and mobile app

### Next Generation Security Panel with Home Automation Capabilities

PowerMaster-360R is a professional modern wireless security and safety control panel, with optional home automation capabilities. It is suitable for residential customers and small to mid-size businesses who want a professional alarm and home automation system in a single platform. It provides outstanding wireless functionality with all peripherals.

Using Tyco's award winning PowerG wireless technology, PowerMaster-360R answers the demands for a professional security system. The combined, optional Z-Wave and Wi-Fi connectivity answers advanced home automation needs.

### PowerG Robustness and Reliability

- Frequency Hopping Spread Spectrum (FHSS)
- Highly secured AES-128 encrypted wireless communication – Surpasses the most demanding industry standards
- Huge transmission range of 2000m (6500ft) line of sight\* – Covers significantly larger premises than traditional systems, without repeaters
- Full two-way synchronized TDMA wireless network – Provides streamlined communication and improved channel efficiency
- Adaptive transmission power – Saves energy and significantly extends battery life

\*Measured line-of-sight transmission range: 2000m (6500ft) at 8m (24ft), 750m (2500ft) at 2m (6.5ft)

## Comprehensive Toolset for Fast and Easy Installation

- Special enrollment button on each device simplifies enrollment procedures
- Installer configuration using virtual keypad application (PC or Android) via standard MicroUSB port or through touchscreen keypad
- Full user experience via mobile application\*
- Visible signal quality indication shown on the sensors – Enables quick and easy installation while maintaining optimal radio performance
- Powerful diagnostic tool indicates RF link quality, based on the previous 24 hours' statistics and on-demand bi-directional measurements, displaying immediate problems and enabling verification of the installation during house setup

## Powerful Tools for Central Monitoring Stations

- Remote enrollment, configuration, and review of all peripherals in the system
- Initiate remote walk test with assistance from anyone in the house
- Remote diagnostics of wireless connection and RF link quality for all peripherals – Based on the previous 24 hours' statistics and on-demand bi-directional measurements

## Green, Energy-saving System

- Up to 5-8 years battery life for all peripherals
- Two-way, synchronized, spread spectrum communication eliminates unnecessary re-transmissions
- Minimum power consumption and pollution due to adaptive transmission power that is determined according to the distance from the panel and level of RF interference

## Specifications

RF network . . . . .	PowerG - Frequency hopping multi-channel (CDMA)
Frequency bands (Mhz) . . . . .	433 – 434 868 – 869 912 – 919
Hopping frequencies . . . . .	8 4 50
Encryption . . . . .	AES-128
Number of zones . . . . .	64
User codes . . . . .	48
Back-up battery . . . . .	12-hour back-up (LiPo, rechargeable battery, 3.7V, 1000mAh)
Dimensions . . . . .	168 x 152 x 42mm (6.61 x 5.98 x 1.65in)
Power supply . . . . .	External
Reporting formats . . . . .	Analog: SIA, Contact ID, Scancom; IP: SIA IP, Visonic PowerNet
Communication . . . . .	IP(10/100 Mbps), 2/3G cellular (Internal SIM card)
Wi-Fi . . . . .	802.11b/g/n, 2.4MHz wireless connectivity
Z-Wave . . . . .	868.4MHz, 908.4MHz, 921.4 Mhz
Certifications . . . . .	CE, EN 50131-1, EN 50131-3 Security Grade 2, environmental class II

\*Mobile application is offered by a 3<sup>rd</sup> party

[www.visonic.com](http://www.visonic.com)

Contact Visonic for further information:  
Email: [info@visonic.com](mailto:info@visonic.com)

Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative.  
© 2017 Tyco Security Products Ltd. All rights reserved. The trademarks and service marks of Tyco, including the Tyco mark and logo and PowerG are the exclusive property of Tyco, and may not be used without permission. All other marks are the property of their respective owners. PowerMaster-360R DATA SHEET ENG (Rev.03). 11-2017